

Via Maltese, 62/64 - 90146 Palermo (PA) - Italia

Tel. 091 685 1784 Mobile +39 351 8753628

e-mail: info @allfoodproject.com website: www.allfoodproject.com.com

C.F. GLLBGI66L21G273C VAT Number 03765550821 Company Registered Number 162241

Estimate No. 6535

05/03/2024

of the

Info	

CALL us for FREE consulting service Tel 091 685 1784 or CHAT with us on Whatsapp +393518753628

Cod. art.	Description	Qty	Price	Discount	Amount
INOXPOWER/ H1	Totem AFP /H1	1		€125.00	
	- Height: 1000 mm - Width: 300 mm - Depth: 300 mm - Weight: 10 kg - Material: 304 or 430 stainless steel				

Optional : - Acciaio inox 304

Technical Sheet

Structure: stainless steelPower supplyDoor opening from right to leftDimensions cm L 80 x P 81.1 x 50.2 hTimer providedThermostat 48 - 260 CCapacity: 4 trays (included)Power 6.9 kwCE standardEnergy saving modeTrays distances 7,5 cmWeight 55 kgDry mode: removal of humidity from the cooking chamberSafety temperature limiterInternal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsAl technology: learns from previous cooking and regulates the pre-heating temperature for the next program.		
Timer providedThermostat 48 - 260 CCapacity: 4 trays (included)Power 6.9 kwCE standardEnergy saving modeTrays distances 7,5 cmWeight 55 kgDry mode: removal of humidity from the cooking chamberSafety temperature limiterInternal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAl technology: learns from previous cooking and regulates	Structure: stainless steel	Power supply
Capacity: 4 trays (included)Power 6.9 kwCE standardEnergy saving modeTrays distances 7,5 cmWeight 55 kgDry mode: removal of humidity from the cooking chamberSafety temperature limiterInternal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAl technology: learns from previous cooking and regulates	Door opening from right to left	Dimensions cm L 80 x P 81.1 x 50.2 h
CE standardEnergy saving modeTrays distances 7,5 cmWeight 55 kgDry mode: removal of humidity from the cooking chamberSafety temperature limiterInternal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAl technology: learns from previous cooking and regulates	Timer provided	Thermostat 48 - 260 C
Trays distances 7,5 cmWeight 55 kgDry mode: removal of humidity from the cooking chamberSafety temperature limiterInternal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAl technology: learns from previous cooking and regulates	Capacity: 4 trays (included)	Power 6.9 kw
Dry mode: removal of humidity from the cooking chamberSafety temperature limiterInternal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAI technology: learns from previous cooking and regulates	CE standard	Energy saving mode
Internal cooking chamber lightingDouble glazingGear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAI technology: learns from previous cooking and regulates	Trays distances 7,5 cm	Weight 55 kg
Gear immersion fansControl panel: 896 storable programsFrom 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAI technology: learns from previous cooking and regulates	Dry mode: removal of humidity from the cooking chamber	Safety temperature limiter
From 1 to 3 cooking stepsHumidity in percentage 0-20406080100%Touch screen control panel with LCD displayAI technology: learns from previous cooking and regulates	Internal cooking chamber lighting	Double glazing
Touch screen control panel with LCD display AI technology: learns from previous cooking and regulates	Gear immersion fans	Control panel: 896 storable programs
	From 1 to 3 cooking steps	Humidity in percentage 0-20406080100%
	Touch screen control panel with LCD display	Al technology: learns from previous cooking and regulates the pre-heating temperature for the next program.



+ Add Product

.....





For countries outside of Italy, shipping costs may vary. We will send you a quotation after receiving this order confirmation.

Pursuant to Legislative Decree 196/2003 we only use your data for the purpose of communicating with existing commercial relations between us. Please check your personal data, VAT number and Tax Code. We are not responsible for any errors.